



SEE DESIGN STANDARD DS336 FOR DEFINITION OF SYMBOL.
 SEE DESIGN STANDARD DS520 FOR DEFINITION OF R & FP No.
 UNLESS OTHERWISE STATED: ALL DIMENSIONS IN MILLIMETRES
 & APPLY BEFORE FINISHING TOL. ±0,25 ANGLES ±2°
 REMOVE SHARP CORNERS - CHAMFER OR R0,5 MAX.
 INTERNAL RADII 0,5 MAX. SURFACE TEXTURE - $\sqrt{Ra\ 3,2}$
 THREADS TO BS 3643 6g/6H. DRAWING PRACTICE TO BS 8888

3rd ANGLE PROJECTION

 DO NOT SCALE

TITLE
MRS 400MM RAIL

RENISHAW MATL R CODE _____

MATERIAL (ENTER R OR FP CODE TO VIEW EQUIVALENT MATERIAL SPEC USING SUPPLIER PORTAL SITE @ WWW.RENISHAW.COM) _____

DRAWN BY JW	DRAWN DATE MAR 15	SHEET 1 OF 1	CHECKED RT
----------------	----------------------	-----------------	---------------

CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF © RENISHAW plc, AND MAY NOT BE COPIED OR USED FOR ANY PURPOSE, OTHER THAN THAT FOR WHICH IT IS SUPPLIED, WITHOUT THE EXPRESS WRITTEN AUTHORITY OF RENISHAW plc.

RENISHAW®

Wotton - under - Edge
 Glos. England.
 GL12 8JR

SCALE
 U.O.S.
 1:2

DRAWING No.
 LA-4192-1003-A

SHEET	1	TITLE	DRG. No.
CONT. ON NEXT SHT.		MRS 400MM RAIL	LA-4192-1003

MOD. ISS.	DETAILS OF CHANGE	CIN	SIGN DATE
A	FIRST ISSUE MODEL: GEOMETRY EQUIVALENT TO A-2098-0942-01	69035	JW MAR 15

RENISHAW

DRAWING MODIFICATION SHEET