



SEE DESIGN STANDARD DS336 FOR DEFINITION OF  SYMBOL. SEE DESIGN STANDARD DS520 FOR DEFINITION OF R & FP No. UNLESS OTHERWISE STATED: ALL DIMENSIONS IN MILLIMETRES & APPLY BEFORE FINISHING TOL. ±0,25 ANGLES ±2° REMOVE SHARP CORNERS - CHAMFER OR R0,5 MAX. INTERNAL RADII 0,5 MAX. SURFACE TEXTURE -  3,2 THREADS TO BS 3643 6g/6H. DRAWING PRACTICE TO BS 8888	3rd ANGLE PROJECTION 	TITLE MRS2 RAIL-TO-LEG BRACKET		DRAWN BY RDT	DRAWN DATE 23/01/15	SHEET 1 OF 1	CHECKED BH
	DO NOT SCALE	RENISHAW MATL R CODE _____	MATERIAL (ENTER R OR FP CODE TO VIEW EQUIVALENT MATERIAL SPEC USING SUPPLIER PORTAL SITE @ WWW.RENISHAW.COM) _____				
CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF © RENISHAW plc, AND MAY NOT BE COPIED OR USED FOR ANY PURPOSE, OTHER THAN THAT FOR WHICH IT IS SUPPLIED, WITHOUT THE EXPRESS WRITTEN AUTHORITY OF RENISHAW plc.	RENISHAW® Wotton - under - Edge Glos. England. GL12 8JR		SCALE U.O.S. 1:1	DRAWING No. LA-6007-0575-A			

SHEET		1	TITLE		DRG. No.		
CONT. ON NEXT SHT.			MRS2 RAIL-TO-LEG BRACKET		LA-6007-0575		
MOD. ISS.		DETAILS OF CHANGE				CIN	SIGN DATE
A		FIRST ISSUE MODEL: GEOMETRY EQUIVALENT TO A-6007-0575-01				FIN 3229	RDT 23/01/15
RENISHAW							
DRAWING MODIFICATION SHEET							