

SAFETY DATA SHEET

Inconel 718

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Trade name Inconel 718 Other names / Synonyms Document No.: H-5800-0929-02-B EN Product no. A-5771-0405 1.2. Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture Metal powder for additive layer manufacture Uses advised against None known. 1.3. Details of the supplier of the safety data sheet Company and address Renishaw plc New Mills Wotton-under-Edge, GL12 8JR, Gloucestershire, United Kingdom +44 (0) 1453 524524 www.renishaw.com E-mail msds@renishaw.com Revision 27/01/2023 SDS Version 1.1 Date of previous version 21/10/2022 (1.0) 1.4. Emergency telephone number The National Poisons Information Centre (NPIC) Public: +353 (0) 1 809 2166 (7 days a week, 8am- 10pm) Healthcare professionals: +353 (0) 1 809 2566 (24 h service) See also section 4 "First aid measures" Emergency contact from supplier: +44 (0) 1453 524524 (UK office hours 08:00 to 17:00 UTC Monday to Thursday, 08:00 to 16:00 Friday)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture Skin Sens. 1; H317, May cause an allergic skin reaction. Carc. 1B; H350, May cause cancer. Repr. 1B; H360F, May damage fertility. STOT RE 1; H372, Causes damage to organs through prolonged or repeated exposure. Aquatic Chronic 3; H412, Harmful to aquatic life with long lasting effects.
2.2. Label elements



Signal word Danger				
Hazard statement(s)				
	, ergic skin reaction. (H317)			
May cause cance				
May damage fert				
Causes damage t	to organs through prolonged o tic life with long lasting effects.		e. (H372)	
Safety statement(s)	5 5	· · ·		
General				
-				
Prevention				
	instructions before use. (P201)			
Do not breathe				
	ection/protective gloves/protec	tive clothing. (P280)		
Response		-		
IF exposed or o	concerned: Get medical advice/ dvice/attention if you feel unwe		13)	
Storage	,	、 ,		
- Disposal				
▼ Disposal Dispose of con	itents/container in accordance	with local regulation	(P501)	
Hazardous substanc		with local regulation		
Nickel	.03			
Cobalt				
Additional labelling				
Restricted to pro-	fessional users			
2.3. Other hazards				
Additional warnings				
	stible dust concentrations in a	ir		
			o meet the criteria classifying th	em as PBT
and/or vPvB.	aute abes not contain any sub-		o meet the enterna classifying th	cill do l bi
	s not contain any substances c	onsidered to be end	ocrine disruptors in accordance	with the
			or Commission Regulation (EU)	
SECTION 5. Compositi	on/information on ingredients			
3.1. ▼Substances				
Not applicable. This	product is a mixture.			
3.2. Mixtures				
Product/substance	Identifiers	% w/w	Classification	Note
Nickel	CAS No.: 7440-02-0	52.0-54.0%	Skin Sens. 1, H317	[1], [3]
	EC No.: 231-111-4		Carc. 2, H351	
	REACH:		STOT RE 1, H372	
	Index No.: 028-002-01-4		Aquatic Chronic 3, H412	
Chromium	CAS No.: 7440-47-3	18.0-20.0%	Aquatic Chronic 4, H413	
	EC No.: 231-157-5		-	

	REACH: Index No.:		
Iron	CAS No.: 7439-89-6 EC No.: 231-096-4 REACH: 01-2119462838-24-XXXX Index No.:	14.8 - 20.9%	
Cobalt	CAS No.: 7440-48-4 EC No.: 231-158-0 REACH: Index No.: 027-001-00-9	0.3%	Skin Sens. 1, H317 Resp. Sens. 1, H334 Muta. 2, H341 Carc. 1B, H350 Repr. 1B, H360F Aquatic Chronic 4, H413

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[3] According to REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

▼ Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Not applicable.

4.2. ▼ Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact. Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

4.3. Indication of any immediate medical attention and special treatment needed

IF exposed or concerned:

Get immediate medical advice/attention.

If skin irritation or rash occurs: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Use class D extinguishing agents on dust, fines or molten metal. Unsuitable extinguishing media: Water, foam, halogenated extinguishing agents.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are: Some metal oxides

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are

released into the atmosphere in sufficient concentration. Avoid direct contact with spilled substances. Evacuate surrounding areas. Eliminate all ignition sources. Ventilate the area.

Wear appropriate personal protective equipment (see section 8).

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Collect spills carefully. Moist the material with water in order to prevent the formation and propagation of dust. Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents. Use spark-proof tools and explosion-proof equipment.

Avoid dust generation.

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

Take precautionary measures against static discharges.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Powder trickling out onto the floor or onto other containers must be prevented.

Avoid the suspension of dust in the air.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Use non-sparking tools. Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Store in tightly closed original container in a dry, cool and well-ventilated place.

Store in accordance with local regulations.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. ▼ Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Nickel

Long term exposure limit (8 hours) (mg/m³): 0.5

Chromium

Long term exposure limit (8 hours) (mg/m³): 2

Annotations:

IOELV = Indicative Occupational Exposure Limit Values are health based limits set under the Chemical Agents Directive (98/24/EC).

Cobalt

Long term exposure limit (8 hours) (mg/m³): 0.02

Annotations:

Sen = Chemical agent which following exposure may cause sensitisation of the respiratory tract and lead to asthma,

rhinitis or extrinsic allergic alveolitis.

2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019).

DNEL

No data available.

PNEC

No data available.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis. Where necessary use lighting and electrical equipment designed for use in atmospheres where flammable vapours or dusts are present, and which can direct static electricity by grounding equipment.

General recommendations

When transferring the materials, dust clouds should be kept at an absolute minimum. Handling should be slow and deliberate. The materials should be transferred from one container to another using a non-sparking, conductive metal scoop.

When mixing the material with other dry ingredients, frictional heat should be avoided. The best type of mixer for a dry mixing operation is one that contains no moving parts, but rather affects a tumbling action, such as a conical blender. Introduction of an inert atmosphere in the blender is highly recommended since dust clouds are generated. All equipment must be well grounded.

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Do not recirculate outlet air that contain the substances.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

8.3. Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

Туре	Class	Colour	Standards	
SL	P3	White	EN149	

Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-	R
Safety shoes		EN ISO 20345	

Hand protection



Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Butyl	0,3	> 480	EN374-2, EN374-3, EN388	

Type Standards Safety glasses with side EN166 shields. EN166



SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties Physical state Powder
Colour Gray
Odour / Odour threshold None
pH Not applicable - product is a solid
Density (g/cm³) 4-6
Relative density Not applicable - product is a solid
Kinematic viscosity Not applicable - product is a solid
Particle characteristics Particle size: < 1.0 mm
Phase changes
Melting point/Freezing point (°C) > 1000 (melting point)
Softening point/range (waxes and pastes) (°C) Does not apply to solids.
Boiling point (°C) No information available as testing has not been completed.
Vapour pressure Not applicable - product is a solid
Relative vapour density Does not apply to solids.
Decomposition temperature (°C) No information available as testing has not been completed.
Data on fire and explosion hazards
Flash point (°C) Does not apply to solids.
Auto-Ignition (°C)
Testing not relevant or not possible due to nature of the product.
Flammability (°C) Testing not relevant or not possible due to nature of the product.
Lower and upper explosion limit (% v/v) Does not apply to solids.
Solubility
Solubility in water Insoluble
n-octanol/water coefficient No information available as testing has not been completed.



5 5	
Solubility in fat (g/L) No information av 9.2. Other information Formation of explosit Yes Evaporation rate (n-b Not applicable - pr Other physical and ch No data available.	utylacetate = 100) roduct is a solid nemical parameters
SECTION 10: Stability ar	nd reactivity
 10.3. Possibility of hazar None known. 10.4. Conditions to avoid Avoid the suspension 10.5. Incompatible mate Strong acids, strong k 10.6. Hazardous decomplation 	d of dust in the air. erials bases, strong oxidizing agents, and strong reducing agents.
SECTION 11: Toxicologi	cal information
11.1. Information on has Acute toxicity Product/substance Test method Species Route of exposure Test Result Other information	zard classes as defined in Regulation (EC) No 1272/2008 Nickel Rat Oral LC50 >5000 mg/kg
Product/substance Test method Species Route of exposure Test Result Other information	Chromium Rat ED50 > 3400 mg/kg
Product/substance Test method Species Route of exposure Test Result Other information	Iron Rat Oral LD50 30000 mg/kg
Product/substance Test method Species Route of exposure Test Result Other information	Cobalt Rat Oral LD50 6171 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

May cause an allergic skin reaction.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

May cause cancer.

Reproductive toxicity

May damage fertility.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Carcinogenic effects: This product contains substances considered or proven to be carcinogenic. The carcinogenic effects may be triggered subsequent to exposure through inhalation, skin contact or ingestion. Reproductive toxicity: This product contains reprotoxic substances, which may harm the reproductive capacity. Adverse effects include: sterility, effects on the sexual function, lowered effective fertility and dysfunctional menstrual

cycle.

Endocrine disrupting properties

None known.

Other information

Nickel has been classified by IARC as a group 2B carcinogen.

Chromium has been classified by IARC as a group 1 carcinogen.

Cobalt has been classified by IARC as a group 2B / 2A (Cobalt metal with tungsten carbide) carcinogen.

Exposure to metal dusts and oxides may cause metal fume fever. Metal fume fever is a temporary flu-like condition characterized by chills, fever, muscle aches and pains, nausea, and vomiting. Typically, the symptoms appear within a few hours after exposure and subside within 2-3 days with no permanent effects.

SECTION 12: Ecological information

12.1. Toxicity

IZ.I. TOXICILY	
Product/substance	Nickel
Test method	
Species	Fish, Oncorhynchus mykiss
Compartment	
Duration	96 hours
Test	LC50
Result	31.7 mg/L
Other information	
Product/substance	Nickel
Test method	
Species	Fish, Pimephales promelas
Compartment	
Duration	96 hours
Test	LC50
Result	3.1 mg/L
Other information	
Product/substance	Nickel
Test method	
Species Compartment	Fish, Brachydanio rerio
Duration	96 hours
Test	LC50
Result	>100 mg/L



Other information				
Product/substance Test method	Nickel			
Species	Algae, Selenastrum capricornutum			
Compartment	Aigae, Selenasti un capitico nutum			
Duration	72 hours			
Test	EC50			
Result	0.18 mg/L			
Other information				
Product/substance	Nickel			
Test method				
Species	Daphnia			
Compartment				
Duration	96 hours			
Test	EC50			
Result	510 µg/L			
Other information				
Product/substance	Iron			
Test method				
Species	Fish			
Compartment				
Duration	96 hours			
Test	LC50			
Result Other information	13.6 mg/L			
Other information				
Product/substance	Cobalt			
Test method Species	Fish, Brachydanio rerio			
Compartment				
Duration	96 hours			
Test				
Result	>100 mg/L			
Other information				
Product/substance	Cobalt			
Test method				
Species	Daphnia, Daphnia magna			
Compartment				
Duration	48 hours			
Test				
Result Other information	3.2 mg/L			
Product/substance	Cobalt			
Test method				
Species Compartment	Algae, Selenastrum capricornutum			
Duration Test	72 hours			
Result	0.05 - 0.26 mg/L			
Other information	0.00 0.20 mg/ 2			
12.2. Persistence and de	paradability			
No data available.	gradability			
	otoptial			
12.3. Bioaccumulative po	Jlenual			
No data available.				
12.4. Mobility in soil				
No data available.				
12.5. Results of PBT and				
This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or				
vPvB.				
12.6. Endocrine disrupti	ng properties			
- - - - - - - -				



None known.

12.7. Other adverse effects

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste. HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity HP 7 - Carcinogenic HP 13 - Sensitising HP 14 - Ecotoxic Dispose of contents/container to an approved waste disposal plant. Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste. EWC code

Not applicable.

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	-	-	-	-	-	-
IMDG	-	-	-	-	-	-
IATA	-	-	-	-	-	-

* Packing group

** Environmental hazards

Additional information

Not dangerous goods according to ADR, IATA and IMDG.

14.6. Special precautions for user

Not applicable.

- 14.7. Maritime transport in bulk according to IMO instruments
 - No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

Nickel

REACH, Annex XVII

Nickel is subject to REACH restrictions, REACH annex XVII (entry 27).

Additional information

Not applicable.

Sources

Protection of Young Persons (Employment) Act, 1996 Maternity Protection Act 1994 (34/1994) with later amendments. SI No 209 of 2015 Chemicals Act (Control of Major Accident Hazards involving Dangerous Substances) Regulations



2015.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H317, May cause an allergic skin reaction.

H334, May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341, Suspected of causing genetic defects.

H350, May cause cancer.

H351, Suspected of causing cancer.

H360F, May damage fertility.

H372, Causes damage to organs through prolonged or repeated exposure.

H412, Harmful to aquatic life with long lasting effects.

H413, May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The safety data sheet is validated by EcoOnline

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en