Product Poly 90 Release Agent

Revision Date 12/10/2016

Revision 1



Safety Data Sheet (SDS)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product Name Poly 90 Release Agent Synonyms, Trade Names No information available.

1.2 Relevant Identified Uses of the Substance or Mixture and Uses Advised Against

Identified Uses Vacuum casting.

Uses Advised Against No uses advised against are identified.

1.3 Details of the Supplier of the Safety Data Sheet

Supplier Renishaw plc

Brooms Road Stone Business Park Stone, Staffordshire ST15 0SH

United Kingdom

Tel: +44 (0) 1785 285000 (during UK office hours 09:00 to 17:00 UTC).

msds@renishaw.com

1.4 Emergency Telephone Number

Contact Person

Emergency Telephone 999 / 911 or local emergency number.

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classifcation of the Substance or Mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards Press. Gas - H280, Flam. Aerosol 1 - H222 Human Health Skin Irrit.2 - H315, STOT SE 3 - H336 Environment Aquatic Chronic 2 - H411

2.2 Label Elements

Contains Not applicable

Label in Accordance With (EC) No.

1272/2008



Signal Word Danger

Hazard Statements H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary Statements Prevention

P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P211 Do not spray on an open flame or other ignition source. P251 Pressurized container: Do not pierce or burn, even after use. P261 Avoid breathing dust/fume/ gas/mist/vapours/spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/eye protection/face protection.

Response

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF.

2.3 Other Hazards

Preparations classified as harmful on the basis of an aspiration hazard need not be labelled as harmful with H304 when placed on the market in aerosol containers or in containers fitted with a sealed spray attachment. (EU-Directive 67/548 Annex VI 9.4).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance

Not applicable.

3.2 Mixtures

Name	Product Identifier	GHS Classification	%
Inentane		Flam. Liq 2- H225, Asp. Tox - H304, STOT SE 3 - H336, Aquatic Chronic 2 - H411	30-60%
· · · · · · · · · · · · · · · · · ·		Flam. Liq 2- H225, Skin Irrit.2 - H315, STOT SE 3 - H336, Asp. Tox - H304, Aquatic Chronic 2 - H411	30-60%
Icarbon dioxide	CAS-No.: 124-38-9 EC No.: 204-696-9	Press. Gas - H280	1-10%

The Full Text for all Hazard Statements Are Displayed in Section 16.

Composition Comments The data shown are in accordance with the latest EC Directives. Note H and P of Annex I

(67/548/EEC) apply for the naphtha in this product.

SECTION 4: FIRST AID MEASURES

4.1	Description	of First Aid Measures	

General Information Provide general first aid, rest, warmth and fresh air. As a general rule, in case of doubt or if

symptoms persist, always call a doctor. Seek medical attention for all burns and eye injuries, regardless how minor they may seem. First aid personnel must be aware of own risk during

rescue.

Inhalation If this product is inhaled and symptoms occur, move the exposed person to fresh air

promptly. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Seek medical attention.

Ingestion Provide fresh air, warmth and rest, preferably in comfortable upright sitting position. Never

give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head low and/or keep airway clear. If swallowed, seek medical advice immediately and show

the container or label. DO NOT induce vomiting!

Skin Contact Remove affected person from source of contamination. Remove contaminated clothing.

Promptly flush contaminated skin with water. Wash skin thoroughly with mild soap and

water. Get medical attention promptly if symptoms occur after washing.

Eye Contact Do not rub eye. If this product contacts the eyes, gently flush eyes with water for at least

fifteen (15) minutes, lifting the upper and lower eyelids occasionally. Avoid contaminating

 $un affected \ eye. \ Seek \ medical \ attention.$

4.2 Most Important Symptoms and Effects, Both Acute and Delayed

General Information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation In case of overexposure, solvents may depress the central nervous system causing headache,

dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of

consciousness.

Ingestion May cause nausea, vomiting, abdominal pain and irritation of the throat. Due to the physical

nature and packaging of this material it is unlikely that swallowing will occur.

Skin Contact May be moderately irritating to skin. Symptoms of exposure may include redness, swelling or

pain.

Eye Contact May cause irritation, redness, and tearing.

4.3 Indication of any Immediate Medical Attention and Special Treatment Needed

Notes to the Physician Treat symptomatically. Due to the physical nature and packaging of this material it is

unlikely that swallowing will occur. In case of ingestion: Aspiration of the swallowed or

vomited product can cause severe pulmonary complications.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Extinguishing Media Use fire-extinguishing media appropriate for surrounding materials. Dry chemical, carbon

dioxide, chemical foam and water spray.

Unsuitable Extinguishing Media Do not use water jet as an extinguisher.

5.2 Special Hazards Arising From the Substance or Mixture

Hazardous Combustion Products In case of fire, toxic gases (CO, CO2,) may be formed. Hydrogen fluoride (HF) may be formed

under fire conditions.

Unusual Fire & Explosion Hazards Aerosols may explode if heated above 50°C. FLAMMABLE. Exposure to fire may cause

containers to rupture/explode.

Specific Hazards If heated, harmful vapours may be formed.

5.3 Advice for Firefighters

Special Fire Fighting Procedures Evacuate personnel to safe areas. Ventilate closed spaces before entering them. Avoid

breathing fire vapours. Keep up-wind to avoid fumes. Fight advanced or massive fires from $\,$

safe distance or protected location. Water spray should be used to cool containers.

Protective Equipment for

Firefighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard

EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: ACCIDENTAL RELEASE MEASURES

<u>6.1 Personal Precautions, Protective Equipment and Emergency Procedures</u>

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all

sources of ignition. Provide adequate ventilation. In case of inadequate ventilation, use

respiratory protection.

Avoid inhalation of vapours and contact with skin and eyes. If necessary evacuate

surrounding areas. Keep unnecessary and unprotected personnel from entering. Read and

follow manufacturer's recommendations.

For Emergency Responders Follow safe handling advice and personal protective equipment recommendations for normal

use of product.

6.2 Environmental Precautions

Environmental Precautions Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled

discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency

or other appropriate regulatory body

6.3 Methods and Material for Containment and Cleaning Up

Spill Clean Up Methods Prevent further leakage or spillage if safe to do so. Ventilate and evacuate the area.

Eliminate all sources of ignition. Wear necessary protective equipment.

Absorb spillage with non-combustible, absorbent material - sand. Keep area evacuated and

free from ignition sources until product has evaporated. Use non sparking tools or

equipment for clean up.

Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. Wash thoroughly after dealing with

a spillage.

6.4 Reference to Other Sections

Reference to Other Sections

See section 1 for emergency contact. For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for Safe Handling

Handling

Keep away from heat, sparks and open flame. Wear suitable personal protective equipment, as detailed in Section 8. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Static electricity and formation of sparks must be prevented. Avoid prolonged or repeated contact.

Avoid spilling, skin and eye contact. Avoid inhalation of vapours. Do not eat, drink or smoke when using the product. Do not wear contact lenses. Do not mix with other chemicals. Pressurised container: Do not pierce or burn, even after use.

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Storage Precautions Keep locked up and out of reach of children. Keep away from heat, sparks, direct sunlight

and open flames. Store in tightly closed original container in a dry, cool and well-ventilated place. Pressurised container: Must not be exposed to temperatures above 50°C Avoid contact

with oxidising agents.

Storage Class Aerosols.

7.3 Specific End Use(s)

Specific End Use(s)
Usage Description

The identified uses for this product are detailed in Section 1. Use only according to directions. Replace and tighten cap after use.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control Parameters

Component	STD	TWA (8 Hrs)		STEL (15mins)		Notes
pentane	WEL	600ppm	1800mg/m3			
pentane	NIOSH	120ppm	350mg/m3	610ppm	1800mg/m3	NIOSH
carbon dioxide	WEL	5000ppm	9150mg/m3	15000ppm	27400mg/m3	
carbon dioxide	NIOSH	5000ppm	9000mg/m3	30000ppm	54000mg/m3	NIOSH

Ingredient Comments

WEL - Workplace Exposure Limits - EH40/2005 Workplace exposure limits. The National Institute for Occupational Safety and Health (NIOSH).

8.2 Exposure Controls







Engineering Measures Provide adequate ventilation, including appropriate local extraction, to ensure that the

defined occupational exposure limit is not exceeded. Use explosion-proof ventilation

equipment.

Respiratory Equipment Where risk assessment shows air-purifying respirators are appropriate a full face respirator

conforming to EN143, and suitable respirator cartridges as a backup to engineering controls. Where aerosols are in use, use self contained breathing apparatus with a type AX filter or appropriate combined filter (e.g. AX-P3), in compliance with EN 371. If the respirator is the

sole means of protection, use a full-face supplied air respirator.

Use respirators and components tested and approved under appropriate government standards such as CEN (EU). Use respiratory protection as specified by an industrial

hygienist or other qualified professional. Change filters frequently.

Hand Protection Selection of the glove material depends on consideration of the penetration times, rates of

diffusion and degradation, and concentration specific to the workplace. Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe:

EN374) is recommended.

Gloves must be inspected prior to use. Suggested material: Nitrile. Consult manufacturer for specific advice on material. Dispose of contaminated gloves after use in accordance with

applicable laws and good laboratory practices.

Eye Protection Wear safety goggles or face shield to prevent any possibility of eye contact. Use equipment

for eye protection tested and approved under appropriate government standards such as EN

166(EU).

Other Protection Wear appropriate clothing to prevent any possibility of skin contact.

Protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. The selected

clothing must satisfy the European norm standard EN 943.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Observe normal

hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.

Wash promptly if skin becomes contaminated.

Process Conditions Ensure that eye flushing systems are located close by in the work place.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on Basic Physical and Chemical Properties

Appearance Liquid under pressure.

Colour Colourless.
Odour Solvent.

Odour Threshold - Lower No information available.

Odour Threshold - Upper No information available.

pH-Value, Conc. Solution No information available.

pH-Value, Diluted Solution No information available.

Melting Point No information available.

Initial Boiling Point and Boiling

Range

No information available.

Flash Point < 0.01 °C

Evaporation Rate No information available.

Flammability State No information available.

Flammability Limit - Lower(%) No information available.

Flammability Limit - Upper(%) No information available.

Vapour Pressure No information available.

Vapour Density (air=1) No information available.

Relative Density 0.7g/cm3 @ 20.00 °C

Bulk Density No information available.

Solubility Insoluble in water.

Decomposition Temperature No information available.

Partition Coefficient; n-

Octanol/Water

No information available.

Auto Ignition Temperature (°C) >200 °C.

Viscosity No information available.

Explosive Properties Aerosols may explode if heated above 50°C.

Oxidising Properties No information available.

9.2 Other Information

Molecular Weight No information available.

Volatile Organic Compound No information available.

Other Information None noted.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity Keep away from incompatibles such as oxidizing agents, acids, and alkalis.

10.2 Chemical Stability

Stability Do not expose to temperatures exceeding 50°C. Protect from direct sunlight.

10.3 Possibility of Hazardous Reactions

Hazardous Reactions Avoid extremes of temperature.

Hazardous Polymerisation Will not polymerise.
Polymerisation Description Not applicable.

10.4 Conditions to Avoid

Conditions to Avoid Heat, sparks, open flames, temperature extremes and direct sunlight.

10.5 Incompatible Materials

Materials to Avoid Avoid contact with oxidising agents, strong alkalis, and strong acids.

10.6 Hazardous Decomposition Products

Hazardous Decomposition Products Hydrogen fluoride (HF) may be released under fire conditions. Fire can release oxides of

carbon dioxide, carbon monoxide and other hydrocarbon products.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on Toxicological Effects

Toxicological Information No toxicological information for the overall finished product.

Acute Toxicity (Oral LD50)

Acute Toxicity (Dermal LD50)

Acute Toxicity (Inhalation LD50)

No information available.

No information available.

Serious Eye Damage/Irritation Product is not classified as an eye irritant.

Skin Corrosion/Irritation No information available.

Respiratory Sensitisation No information available. Skin Sensitisation No information available.

Germ Cell Mutagenicity No information available.

Carcinogenicity No information available.

Specific Target Organ Toxicity - Single Exposure:

STOT - Single Exposure No information available.

Specific Target Organ Toxicity - Repeated Exposure:

STOT - Repeated Exposure No information available.

In case of overexposure, solvents may depress the central nervous system causing headache,

dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of

consciousness.

Ingestion May cause nausea, vomiting, abdominal pain and irritation of the throat. Due to the physical

nature and packaging of this material it is unlikely that swallowing will occur.

Skin Contact May be moderately irritating to skin. Symptoms of exposure may include redness, swelling or

oain.

Eye Contact May cause irritation, redness, and tearing.

Waste Management When handling waste, consideration should be made to the safety precautions applying to

handling of the product. Do not puncture or burn even when empty.

Routes of Entry No information available.

Target Organs Eyes, skin, digestive system, respiratory system, central nervous system.

Aspiration Hazards: No information available. Reproductive Toxicity: No information available.

Name	LD50 Oral	LD50 Dermal	LD50 Inhalation
Naphtha (petroleum), hydrotreated light (benzene<0.1%)	>5000.00mg/kg Rat		

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Acute Toxicity - Fish No information available.
Acute Toxicity - Aquatic No information available.

Invertebrates

Acute Toxicity - Aquatic Plants

Acute Toxicity - Microorganisms

Chronic Toxicity - Fish

Chronic Toxicity - Aquatic

No information available.

No information available.

No information available.

Invertebrates

Chronic Toxicity - Aquatic Plants No information available.
Chronic Toxicity - Microorganisms No information available.

Ecotoxicity - Microorganisms No information available.

Ecotoxicity The product contains a substance which is toxic to aquatic life with long lasting effects.

Eco Toxilogical Information The product contains a substance which is harmful to aquatic organisms.

12.2 Persistence and Degradability

Degradability

Biological Oxygen Demand

Chemical Oxygen Demand

No information available.

No information available.

12.3 Bioaccumulative Potential

Bioaccumulative Potential No data available on bioaccumulation.

Bioacculmation Factor No information available.
Partition Coefficient; n- No information available.

Octanol/Water

12.4 Mobility in Soil

Mobility No information available.

12.5 Results of PBT and vPvB Assessment

Results of PBT and vPvB Assessment No information available.

12.6 Other Adverse Effects

Other Adverse Effects None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Management When handling waste, consideration should be made to the safety precautions applying to

handling of the product. Do not puncture or burn even when empty.

13.1 Waste Treatment Methods

Disposal Methods

Dispose of waste and residues in accordance with local authority requirements, and in accordance with all local, national and international regulations. For waste disposal, use a licensed industrial waste disposal agent.

SECTION 14: TRANSPORT INFORMATION

14.1 UN Number

 UN No. (ADR)
 UN1950

 UN No. (IMDG)
 UN1950

 UN No. (IATA)
 UN1950

14.2 UN Proper Shipping Name

ADR Proper Shipping Name AEROSOLS, IMDG Proper Shipping Name AEROSOLS

IATA Proper Shipping Name AEROSOLS, FLAMMABLE

14.3 Transport Hazard Class(es)

ADR Class 2.1

IMDG Class 2+ - See SP63

IATA Class 2.1

Transport Labels



14.4 Packing Group

ADR/RID/ADN Packing Group <none>
IMDG Packing Group <none>
IATA Packing Group <none>

14.5 Environmental Hazards

ADR Yes IMDG Yes IATA Yes

14.6 Special Precautions for User

EMS F-D, S-U
Emergency Action Code A145 A153
Hazard No. (ADR) <none>
Tunnel Restriction Code (D)

14.7 Transport in Bulk According to Annex II of MARPOL73/78 and the IBC Code

SECTION 15: REGULATORY INFORMATION

EU Legislation

15.1 Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments. The UN Globally Harmonized System (GHS) Safety

Data Sheet format (Annex IV) is implemented as Annex II of REACH EU No 453/2010 of 20th

May 2010 amending regulation (EC) No 1907/2006.

Approved Code of Practice Workplace Exposure Limits Guidance Note EH40/2005.

Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

General Information This Safety Data Sheet is in accordance with Reach Regulation (EC) No 453/2010.

Revision Comments This is a first issue.
Revision Date 12/10/2016

Revision 1
Safety Data Sheet Status Approved.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

H315 Causes skin irritation.

H280 Contains gas under pressure; may explode if heated.

H222 Extremely flammable aerosol.

Disclaimer

Hazard Statements In Full

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.